

Lithium Battery

51.2V 100AH 5.12KWH

· Safety and Intelligent

Long life LiFePO4 cells, high energy density, build in BMS and passive protection

Easy to Install and Use

Modular design, simple operation

· Long Life Span

10 years design life, more than 6000cycles

Adaptable to Harsh Environment Adapt to wide range of temperature and humidity

· Support Bluetooth/WIFI function (optional)

Can be controlled remotely to reduce operation and maintenance costs

· Multi-scenario application

Household use, small industrial and commercial applications



Technical Parameters

Nominal voltage	51.2\
Nominal capacity	100Ah
Energy	5120wh
Interal Resistance	≤200mΩ
Cycle Life	>6000 cycles @ 0.2C 80%D.O.E
Months Self Discharge	<3%
Efficiency of Charge	99.5%@ 0.20
Effciency of Discharge	96-99%@ 10
Charge Voltage	58.4±0.5\
Charge Mode	cc/cv
Charger Current	204
Max Charge Current	1004
Charge Cut-off Voltage	58.4
Continuous discharge Current	204
max discharge Current	1004
Discharge Cut-off Voltage	43.2\
Charge Temperature	0℃ to 45℃
Discharge Temperature	-20 ℃ to 55 ℃
Storage Temperature	-10°C to 40°C
Water Dust Resistance	IP20
Cell & Method	EVE 3.2V100Ah-16S1
Terminal	1004
Protocol (optional)	RS232/RS485/CAN/BLUETOOTH/WIF
BMS	1004
Safety & Certification	CELL:UL1642/UL1973/IEC62619/CE/CB/UN38.3/UL9540/ROHS/REACH
Size (mm)	550*482*133(D*W*H
Net weight (kg)	47KG
Wooden box package size (mm)	940*555*405
Quantity of loading	120pcs/20ft 240pcs/40f

Notes

- *1 Test conditions: Based on the factory date, charge and discharge rate at 0.2C at 100% discharge depth (DoD) and 25 $^\circ$ C
- $^{*}2$ The weight of the battery module is based on the actual product, with a tolerance of \pm 3% allowed
- *3 The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance

Compatibility Inverters



















